


Emergy Brick Pro Mini 1,5-840-170lm AST



Technical Details:

Luminous Flux:	170 lm
LED Output:	1.5 W
Light Yield:	113 lm/W
Light Temperature:	4000 K
Light Color:	daylight
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	6
Ignition Time:	<1 s
Input Current:	AC 220-240VV, 50/60Hz
Power Consumption:	2 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	0°C - 40°C
Storage Temperature:	0°C - 40°C

Dimensions:	199,5x95x45,5 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	Polycarbonat
Cover:	clear
Net Weight:	258 g
Luminaire Type:	Rettungszeichenleuchte
Viewing Distance EN1838:	≥12 m
Included Signs:	Pfeil links rechts oben unten
Testing Facility:	automatischer Selbsttest
Battery Warranty:	2
Discharge Duration:	≥3 h
Battery Type:	Li-Ion
Battery Current:	2500 mA
Battery Charge Duration:	12 h
Initial Charge Duration:	24 h
Charging Power Consumption:	3 W
Battery Cell Quantity	1
Luminous Flux in Battery Mode:	135 lm
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012, Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Type of Packaging:	box
Dimensions of Packaging:	205x100x54
Weight incl. Packaging:	0.32 kg
Content Master Package:	36

Information and Downloads:



Weight Master Package:	12,15 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B30
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4260733770267
inkl. Batterie Accupack	
Autom.Dauertest jährlich, Funktionstest wöchentl.	
kompakte Abmessungen	