

Exita Blade 1,5-857-270lm SC WH



Technical Details:

Luminous Flux:	270 lm
LED Output:	1.5 W
Light Yield:	180 lm/W
Light Temperature:	5700 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Light Emission:	
LED-Chip:	SMD 2835
Number of LED:	24
Ignition Time:	<0,5 s
Input Current:	AC 220-240VV, 70mA, 50/60Hz
Power Consumption:	2 W
Contains Driver:	✓
Power Factor (PF):	>0.5
Input Driver:	terminal
Input Lamp:	terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Storage Temperature:	0°C - 50°C

Dimensions:	341x46x247 mm
Mounting:	Decke
Pivot Range tilt:	90 °
IP Class:	20
IK Code:	07
Housing Color	white
Housing Material:	Polycarbonat/PMMA
Special Feature of Housing:	Built-in/built-on housing
Cover:	clear
Net Weight:	1000 g
Luminaire Type:	Rettsungszeichenleuchte
Viewing Distance EN1838:	≥30 m
Sign Visible from Both Sides:	
Included Signs:	Pfeil oben
Testing Facility:	automatischer Selbsttest
Battery Warranty:	3
Discharge Duration:	≥3 h
Battery Type:	Li-Ion
Battery Current:	2500 mA
Battery Charge Duration:	8 h
Initial Charge Duration:	16 h
Charging Power Consumption:	5 W
Battery Cell Quantity	1
Luminous Flux in Battery Mode:	270 lm
Standards for emergency luminaires:	DIN EN 60598-2-22, DIN EN 62034: 2012, Zeichen nach ISO 7010, Anforderung nach DIN EN 50172
Certified By:	LIA
Type of Packaging:	box

Information and Downloads:



Content Master Package:	12
Dimensions of Master Package:	370x352x541 mm
Weight Master Package:	15,1 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4260733770021
Einschaltstrom Inrush current: 9A/280us @230vac	
autom. Selbsttest: 30s /Woche, Langzeit: 1 x year	
auto selftest: weekly 30s, long duration: 1 x year	
Über- und Entladeschutz, greene Status LED, Taster	