
Technical Data Sheet


Order number: LG14323DIM

Vivra Style 36-840-4000LM 0-10V DIM WH









Technical Details:

Luminous Flux:	4000 lm
LED Output:	34 W
Light Yield:	114 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥81 Ra
Color Consistency (SDCM):	<1
Beam Angle:	110 °
Unified Glare Rating (UGR):	<19
Light Emission:	
Dimmable:	✓
Method of Dimming:	1-10V
LED-Chip Manufacturer:	Jifei
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 55°C

Dimensions:	1200x300x22 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Driver built into frame
Net Weight:	2929 g
Type of Packaging:	box
Dimensions of Packaging:	1390x70x355
Weight incl. Packaging:	3.596 kg
Content Master Package:	4
Dimensions of Master Package:	1410x315x365 mm
Weight Master Package:	15,43 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,D
Barcode:	4250557819693
Lichtaustritt: 30% nach oben, 70% nach unten	
light distribution: 30% up, 70% down	
Inkl. Anschlussrosette	
inkl. terminal box	
Dimmbar	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

