


Estella VARIO CCT 80-927-950-9320LM Dim Sensor



Technical Details:

Luminous Flux:	8800 lm
Light Yield:	114 lm/W
Light Temperature:	2700-5000 K
Light Color:	Vario CCT
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<2
Beam Angle:	110x90 °
Unified Glare Rating (UGR):	<16
Light Emission:	
Dimmable:	✓
Method of Dimming:	Push-Dim
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	77 W
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.95
Input Driver:	cable with plug
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	600x300x1950 mm
Mounting:	ground
IP Class:	20
Housing Color	silver
Housing Color (RAL Code):	similar 9006
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	Steel base
Cover:	prismatic
Net Weight:	13200 g
Type of Packaging:	box
Dimensions of Packaging:	1100x365x125
Weight incl. Packaging:	15.3 kg
Content Master Package:	1
Dimensions of Master Package:	1100x365x125 mm
Weight Master Package:	15,3 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,SELV
Barcode:	4250557823577
LSS: B10 18 Leuchten, B16: 20 Leuchten	
Vario CCT: 2700K bis 5000K	
daylightdimmung automatisch	
Bewegungssensor, deaktivierbar	
zweigeteilter Mast, Sensor Touch Pad	

Information and Downloads:



