


# NOVALOOP Ring Light 120060-60-830-6600lm Dali



## Technical Details:

|                              |                        |
|------------------------------|------------------------|
| Luminous Flux:               | 6600 lm                |
| Light Yield:                 | 110 lm/W               |
| Light Temperature:           | 3000 K                 |
| Light Color:                 | warmwhite              |
| Color Rendering Index:       | ≥80 Ra                 |
| Color Consistency (SDCM):    | <3                     |
| Beam Angle:                  | 120 °                  |
| Unified Glare Rating (UGR):  | <22                    |
| Light Emission:              | downward               |
| Dimmable:                    | ✓                      |
| Method of Dimming:           | DALI                   |
| LED-Chip Manufacturer:       | Everlight              |
| LED-Chip:                    | SMD 2835               |
| Ignition Time:               | <0,5 s                 |
| Input Current:               | AC 220 - 240V, 50/60Hz |
| Power Consumption:           | 60 W                   |
| Contains Driver:             | ✓                      |
| Driver Manufacturer:         | Powergear              |
| Power Factor (PF):           | >0.97                  |
| Input Driver:                | lighting track         |
| Output of Driver:            | DC 5-38V, 1600mA       |
| CC/CV:                       | CC                     |
| Input Lamp:                  | Terminal               |
| Switching Cycles:            | >100.000               |
| Electrical Protection Class: | II                     |
| Ambient Temperature (TA):    | -20°C - 35°C           |
| Storage Temperature:         | -20°C - 45°C           |

|                                            |                  |
|--------------------------------------------|------------------|
| Dimensions:                                | 1200x60 mm       |
| Mounting:                                  | Deckenabhängung  |
| Montageart:                                | surface mounted  |
| IP Class:                                  | 20               |
| Housing Color                              | white            |
| Housing Material:                          | aluminum         |
| Coating:                                   | powder-coated    |
| Cover:                                     | opal             |
| Type of Packaging:                         | box              |
| Dimensions of Packaging:                   | 1250x1250x100    |
| Content Master Package:                    | 1                |
| Product Line:                              | Advance Line     |
| Warranty                                   | 5 years          |
| Operating Hours:                           | 79.000 h L80/B20 |
| Disposal Obligation:                       | ✓                |
| Customs Tariff Number:                     | 9405119090       |
| Certifications                             | CE,LM80,SELV,D   |
| inkl. 200cm Seilabhängung                  |                  |
| incl. 2 x Intrack-Driver Dali 2.0 dimmable |                  |

