


NOVALOOP Ring Light 60060-36-830-3800lm Dali



Technical Details:

Luminous Flux:	3850 lm
Light Yield:	120 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI
LED-Chip Manufacturer:	Everlight
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	32 W
Contains Driver:	✓
Power Factor (PF):	>0.97
Input Driver:	lighting track
Output of Driver:	DC 5-38V, 900mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 35°C
Storage Temperature:	-20°C - 45°C

Dimensions:	600x60 mm
Mounting:	Deckenabhängung
Montageart:	surface mounted
IP Class:	20 (20 room side)
Housing Color	black matt
Housing Material:	aluminum
Coating:	powder-coated
Cover:	opal
Net Weight:	3730 g
Type of Packaging:	box
Dimensions of Packaging:	650x650x100
Weight incl. Packaging:	4.66 kg
Content Master Package:	1
Dimensions of Master Package:	600x650x100 mm
Weight Master Package:	4,66 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	79.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,SELV
Barcode:	4250557827308
200cm Seilabhängung + Deckendose	
DALI Dimmung	

Information and Downloads:

