


Axea Eco Move Mini 12-840-1350lm



Technical Details:

Luminous Flux:	1350 lm
LED Output:	12 W
Light Yield:	113 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	24 °
Light Emission:	downward
LED-Chip Manufacturer:	Cree
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 120mA, 50/60Hz
Power Consumption:	12 W
Contains Driver:	✓
Driver Manufacturer:	Philips
Power Factor (PF):	>0.54
Input Driver:	terminal
Output of Driver:	DC 20 - 36V, 300mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II

Dimensions:	89x76 mm
Installation Depth:	76 mm
Cut-Out Dimensions:	77 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	350 °
Pivot Range tilt:	80 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	273 g
Type of Packaging:	box
Dimensions of Packaging:	105x90x115
Weight incl. Packaging:	0.243 kg
Content Master Package:	30
Dimensions of Master Package:	450x320x240 mm
Weight Master Package:	10,10 kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	30.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,D
Barcode:	4250557819334

Storage Temperature:	-20°C - 55°C
----------------------	--------------

Information and Downloads:

