


Dola Square 35-830-2950LM



Technical Details:

Luminous Flux:	2950 lm
LED Output:	33 W
Light Yield:	84 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	36 °
Light Emission:	downward
LED-Chip Manufacturer:	Citizen
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	35 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 26 - 45V, 800mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 55°C

Dimensions:	185x185x163 mm
Installation Depth:	165 mm
Cut-Out Dimensions:	163x163 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	300 °
Pivot Range tilt:	30 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	1615 g
Type of Packaging:	box
Dimensions of Packaging:	210x240x210
Weight incl. Packaging:	1.786 kg
Content Master Package:	8
Dimensions of Master Package:	440x440x490 mm
Weight Master Package:	14,99 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	40.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808857

Information and Downloads:

