Technical Data Sheet

Order number: LG5801.1

Fenestra Circle MKII 180 11-830-640LM





Technical Details:

Luminous Flux:	640 lm
LED Output:	11 W
Light Yield:	58 lm/W
Light Temperature:	3200 K
Light Color:	warmwhite
Color Rendering Index:	≥85 Ra
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 3528
Number of LED:	108
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	11 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 18 - 22V, 260mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>15.000
Ambient Temperature (TA):	-20°C - 50°C

Dimensions:	180x20 mm
Installation Depth:	20 mm
Cut-Out Dimensions:	163 mm
Mounting:	Decke
IP Class:	43
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	399 g
Type of Packaging:	box
Dimensions of Packaging:	305x55x285
Weight incl. Packaging:	0.607 kg
Content Master Package:	28
Dimensions of Master Package:	640x430x600 mm
Weight Master Package:	18,48 kg
Warranty	3 years
Operating Hours:	35.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809267

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de