



Fenestra Circle Advance 180 15-830-1220LM



Technical Details:

Luminous Flux:	1220 lm
LED Output:	13.5 W
Light Yield:	81 lm/W
Light Temperature:	2800 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	110 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	72
Ignition Time:	<0,5 s
Power Consumption:	15 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.556
Input Driver:	terminal
Output of Driver:	DC 25-38V, 350mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	180x13 mm
Installation Depth:	18 mm
Cut-Out Dimensions:	168-172 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	43
IK Code:	04
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	IP43 raumseits sonst IP20
Cover:	opal
Net Weight:	313 g
Type of Packaging:	box
Dimensions of Packaging:	270x240x35
Weight incl. Packaging:	0.464 kg
Content Master Package:	30
Dimensions of Master Package:	555x265x575 mm
Weight Master Package:	13,2 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV,ENEC,LM80,SELV
Barcode:	4250557811031

Information and Downloads:

