

Fina Square 225 18-830-1690LM



Technical Details:

Luminous Flux:	1570 lm
LED Output:	18 W
Light Yield:	87 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	110 °
Unified Glare Rating (UGR):	<26
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 240mA, 50/60Hz
Power Consumption:	18 W
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.9
Input Driver:	cable with flying leads
Output of Driver:	DC 40-63V, 300mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>25.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	225x225x22 mm
Installation Depth:	22 mm
Cut-Out Dimensions:	200x200 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	40
IK Code:	06
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	574 g
Type of Packaging:	box
Weight incl. Packaging:	0.661 kg
Content Master Package:	20
Dimensions of Master Package:	495 x 460 x250 mm
Weight Master Package:	14,0 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808314

Information and Downloads:



