


Integra Eco round 30-840-2700LM



Technical Details:

Luminous Flux:	2700 lm
LED Output:	28 W
Light Yield:	90 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	36 °
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 22 - 44V, 700mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	175x140 mm
Cut-Out Dimensions:	155 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	350 °
Pivot Range tilt:	30 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	1201 g
Type of Packaging:	box
Dimensions of Packaging:	190x180x190
Weight incl. Packaging:	1.335 kg
Content Master Package:	12
Dimensions of Master Package:	405x405x547 mm
Weight Master Package:	16,71 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	40.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557807218

Information and Downloads:



