


Integra SMD 45-830-3950LM UGR<19



Technical Details:

Luminous Flux:	3950 lm
LED Output:	45 W
Light Yield:	88 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	65 °
Unified Glare Rating (UGR):	<17
Light Emission:	downward
LED-Chip Manufacturer:	Nichia
Number of LED:	65
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50Hz
Power Consumption:	45 W
Power Factor (PF):	>0.95
Output of Driver:	DC 36 - 42V, 1050mA
CC/CV:	CC
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	215x125 mm
Installation Depth:	125 mm
Cut-Out Dimensions:	200 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	865 g
Type of Packaging:	box
Weight incl. Packaging:	1.131 kg
Content Master Package:	9
Dimensions of Master Package:	695x250x530 mm
Weight Master Package:	10,9 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557804521

Information and Downloads:

