

Integra Square Recessed Spotlight



Technical Details:

Luminous Flux:	2800 lm
LED Output:	35 W
Light Yield:	74 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	36 °
Swappable Reflector:	✓
Light Emission:	downward
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Driver Manufacturer:	Tridonic
Power Factor (PF):	>0.94
Input Driver:	terminal
Output of Driver:	DC 20 - 90V
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	180x180x170 mm
Cut-Out Dimensions:	161x163 mm
Mounting:	Decke
Pivot Range pan:	350 °
Pivot Range tilt:	50 °
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	1169 g
Type of Packaging:	box
Weight incl. Packaging:	1.281 kg
Warranty	3 years
Operating Hours:	40.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557806983

Information and Downloads:



