


Varia RC Downlight Gehäuse 40W-WH incl. Driver



Technical Details:

Swappable Reflector:	✓
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	40 W
Contains Driver:	✓
Driver Manufacturer:	AGT
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 32-42V, 700-1000mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-10°C - 45°C
Storage Temperature:	-20°C - 55°C

Dimensions:	197x160 mm
Cut-Out Dimensions:	165-185 mm
Mounting:	Decke
Montageart:	recessed
Pivot Range pan:	355 °
Pivot Range tilt:	30 °
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9003
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Net Weight:	1586 g
Type of Packaging:	box
Weight incl. Packaging:	1.859 kg
Content Master Package:	4
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557822938
Gehäuse zur Aufnahme von LED-Modul, Linse, Blende	
housing to carry LED module, lens and bezel	
Power Select: 28, 32, 36, 40 Watt	
wechselbarer Frontring	
schwenkbar 30°	

Information and Downloads:

