Technical Data Sheet

**Order number: LG91052**

# KUBIX 10-930-32-750LM DIM







## Technical Details:

| | |
|---|---|
| **Luminous Flux:** | 750 lm |
| **LED Output:** | 9 W |
| **Light Yield:** | 75 lm/W |
| **Light Temperature:** | 3000 K |
| **Light Color:** | warmwhite |
| **Color Rendering Index:** | ≥90 Ra |
| **Color Consistency (SDCM):** | <3 |
| **Beam Angle:** | 32 ° |
| **Unified Glare Rating (UGR):** | <16 |
| **Light Emission:** | downward |
| **Dimmable:** | ✓ |
| **Method of Dimming:** | "Triac Phasenan-/abschnitt" |
| **LED-Chip Manufacturer:** | Bridgelux 3535 |
| **LED-Chip:** | High-Power |
| **Number of LED:** | 4 |
| **Ignition Time:** | <0,5 s |
| **Power Consumption:** | 10 W |
| **Contains Driver:** | ✓ |
| **Driver Manufacturer:** | Kegu |
| **Power Factor (PF):** | >0.5 |
| **Input Driver:** | terminal |
| **Output of Driver:** | DC 12V, 700mA |
| **CC/CV:** | CC |
| **Input Lamp:** | terminal |
| **Switching Cycles:** | >100.000 |
| **Electrical Protection Class:** | II |

| | |
|---|---|
| **Dimensions:** | 67x67x85 mm |
| **Mounting:** | Decke |
| **Montageart:** | surface mounted |
| **IP Class:** | 20 |
| **Housing Color** | black |
| **Housing Material:** | aluminum |
| **Cover:** | Lens |
| **Net Weight:** | 328 g |
| **Type of Packaging:** | box |
| **Weight incl. Packaging:** | 0.363 kg |
| **Content Master Package:** | 40 |
| **Dimensions of Master Package:** | 420x345x225 mm |
| **Weight Master Package:** | 14,64 kg |
| **Product Line:** | Advance Line |
| **Warranty** | 3 years |
| **Operating Hours:** | 50.000 h L80/B20 |
| **Disposal Obligation:** | ✓ |
| **Customs Tariff Number:** | 9405119090 |
| **Certifications** | CE |
| **Barcode:** | 4250557823010 |
| Ideal für Wohnräume und Büro | |
| Perfect forresidential applications and office | |
| Geringe Blendung und gerichtetes Licht | |
| Low glare rate and concentrated light beams | |

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

| | |
|---|---|
| **Storage Temperature:** | -20°C - 50°C |

Information and Downloads: