

Yola Brick Wall Light 300-15W-CCT Select BK 1100lm Triac Dim IP65



Technical Details:

| | |
|------------------------------------|------------------------------|
| Luminous Flux: | 1100 lm |
| Light Yield: | 73 lm/W |
| Light Temperature: | 2700,3000,4000 K |
| Light Color: | CCT Select |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <5 |
| Light Emission: | |
| Dimmable: | ✓ |
| Method of Dimming: | "Triac Phasen-an-/abschnitt" |
| LED-Chip: | SMD 2835 |
| Ignition Time: | <1 s |
| Power Consumption: | 15 W |
| Contains Driver: | ✓ |
| Power Factor (PF): | >0.9 |
| Input Driver: | terminal |
| CC/CV: | CC |
| Input Lamp: | Terminal |
| Switching Cycles: | >100.000 |
| Compatible with Emergency Current: | ✓ |
| Ambient Temperature (TA): | -20°C - 45°C |
| Storage Temperature: | -40°C - 60°C |

| | |
|---|--------------------------|
| Dimensions: | 300x100x60 mm |
| Mounting: | Wand |
| Montageart: | surface mounted |
| IP Class: | 65 |
| IK Code: | 03 |
| Housing Color | black |
| Housing Color (RAL Code): | similar 9005 |
| Housing Material: | aluminum |
| Coating: | powder-coated |
| Special Feature of Housing: | Glasabdeckung oben unten |
| Cover: | frosted |
| Net Weight: | 1127 g |
| Type of Packaging: | box |
| Weight incl. Packaging: | 1.279 kg |
| Content Master Package: | 12 |
| Dimensions of Master Package: | 505xx335x270 mm |
| Weight Master Package: | 15,91 kg |
| Product Line: | Advance Line |
| Warranty | 3 years |
| Operating Hours: | 50.000 h L70/B50 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405499090 |
| Certifications | CE |
| Barcode: | 4250557823683 |
| Direkte und indirekte Ausleuchtung sep. schaltbar | |
| Farbwahlschalter CCT-Select: 2700K, 3000K, 4000K | |
| Abstrahlwinkel: 115° x 60° (40° asym. nach vorne) | |
| dekorative Wandleuchte für kreatives Lichtspiel | |

Information and Downloads:

