


Rotura Square 600 48-830-4800LM



Technical Details:

Luminous Flux:	4400 lm
LED Output:	48 W
Light Yield:	92 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 100-270V, 600mA, 50/60Hz
Power Consumption:	48 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 27-42V, 1200mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 35°C

Dimensions:	600x600x40 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Net Weight:	3690 g
Weight incl. Packaging:	3.903 kg
Content Master Package:	5
Dimensions of Master Package:	690 x260 x655 mm
Weight Master Package:	27,0 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808178

Information and Downloads:



