


Rotura Square 400 38-840-2800LM



Technical Details:

Luminous Flux:	2800 lm
LED Output:	30 W
Light Yield:	74 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 100-270V, 600mA, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.92
Input Driver:	cable with flying leads
Output of Driver:	DC 27-42VV, 1200mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 35°C

Dimensions:	400x400x40 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	Surface-mounted housing
Cover:	opal
Net Weight:	2447 g
Dimensions of Packaging:	420x425x45
Weight incl. Packaging:	2.655 kg
Content Master Package:	5
Dimensions of Master Package:	440x270x440 mm
Weight Master Package:	13,53 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557808192

Information and Downloads:



