


Rotura Square 600 48-840 mit Klammern



Technical Details:

Luminous Flux:	4800 lm
LED Output:	46 W
Light Yield:	100 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220-240V, 50/60Hz
Power Consumption:	48 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 27-42V, 1200mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 35°C

Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
IK Code:	03
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	Einbaugehäuse
Cover:	opal
Net Weight:	3441 g
Weight incl. Packaging:	3.903 kg
Content Master Package:	5
Dimensions of Master Package:	690x 260 x 6550 mm
Weight Master Package:	27,0 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557811543

Information and Downloads:

