


Grandeia 48-840-2900LM IP44



Technical Details:

Luminous Flux:	2900 lm
LED Output:	45 W
Light Yield:	60 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	120 °
Unified Glare Rating (UGR):	<24
Light Emission:	downward
LED-Chip Manufacturer:	Epistar
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50Hz, DC 178-230V
Power Consumption:	48 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 27-35V, 1440mA
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	454x105 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
Housing Color	white
Housing Material:	aluminum
Coating:	lacquered
Cover:	opal
Net Weight:	2300 g
Type of Packaging:	box
Dimensions of Packaging:	110x460x460
Weight incl. Packaging:	2.7 kg
Content Master Package:	5
Dimensions of Master Package:	580x480x480 mm
Weight Master Package:	14,17 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,SELV
Barcode:	4250557804118
Leuchte geeignet f. Notstrom an DC Zentralbatterie	
Luminaire can work on DC central emergency battery	
Vorbereitet für Master/Slave Betrieb L + L1	

Information and Downloads:

