
Technical Data Sheet

Order number: LG5863

IRA-M 18-840-1530LM-IP44







Technical Details:

Luminous Flux:	1530 lm
LED Output:	17 W
Light Yield:	85 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	18 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-20°C - 50°C

Dimensions:	360x92 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	44
Housing Color	white
Housing Material:	steel
Coating:	powder-coated
Cover:	opal
Net Weight:	658 g
Type of Packaging:	box
Dimensions of Packaging:	400x400x100
Weight incl. Packaging:	1 kg
Content Master Package:	5
Dimensions of Master Package:	535x420x425 mm
Weight Master Package:	6, kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,D
Barcode:	4250557818375
IP44 raumseits/room side	
weiche, gleichmäßige Ausleuchtung	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de