

# IRA-L 22-840-1980LM-IP44



## Technical Details:

|                              |                        |
|------------------------------|------------------------|
| Luminous Flux:               | 1980 lm                |
| LED Output:                  | 21 W                   |
| Light Yield:                 | 90 lm/W                |
| Light Temperature:           | 4000 K                 |
| Light Color:                 | neutralwhite           |
| Color Rendering Index:       | ≥80 Ra                 |
| Color Consistency (SDCM):    | <4                     |
| Beam Angle:                  | 120 °                  |
| Light Emission:              | downward               |
| LED-Chip:                    | SMD                    |
| Ignition Time:               | <1 s                   |
| Input Current:               | AC 200 - 240V, 50/60Hz |
| Power Consumption:           | 22 W                   |
| Contains Driver:             | ✓                      |
| Power Factor (PF):           | >0.9                   |
| Input Driver:                | terminal               |
| CC/CV:                       | CC                     |
| Input Lamp:                  | Terminal               |
| Switching Cycles:            | >50.000                |
| Electrical Protection Class: | II                     |
| Ambient Temperature (TA):    | -20°C - 40°C           |
| Storage Temperature:         | -20°C - 50°C           |

|                                   |                  |
|-----------------------------------|------------------|
| Dimensions:                       | 410x103 mm       |
| Mounting:                         | ceiling,wall     |
| IP Class:                         | 44               |
| Housing Color                     | white            |
| Housing Material:                 | steel            |
| Coating:                          | powder-coated    |
| Cover:                            | opal             |
| Net Weight:                       | 807 g            |
| Type of Packaging:                | box              |
| Dimensions of Packaging:          | 450x450x115      |
| Weight incl. Packaging:           | 1.234 kg         |
| Content Master Package:           | 5                |
| Dimensions of Master Package:     | 600x470x475 mm   |
| Weight Master Package:            | 7,29 kg          |
| Product Line:                     | Essential Line   |
| Warranty                          | 3 years          |
| Operating Hours:                  | 50.000 h L70/B50 |
| Disposal Obligation:              | ✓                |
| Customs Tariff Number:            | 9405499090       |
| Certifications                    | CE               |
| Barcode:                          | 4250557818382    |
| IP44 raumseits/room side          |                  |
| weiche, gleichmäßige Ausleuchtung |                  |

## Information and Downloads:

