


Ostrea 24-830-1670LM



Technical Details:

Luminous Flux:	1670 lm
LED Output:	24 W
Light Yield:	70 lm/W
Light Temperature:	2800 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 5630
Ignition Time:	<1 s
Input Current:	AC 110 - 240V, 50/60Hz
Power Consumption:	24 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 40°C

Dimensions:	395x113 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20
Housing Color	white
Housing Material:	steel
Coating:	lacquered
Cover:	opal
Net Weight:	1280 g
Type of Packaging:	box
Dimensions of Packaging:	440x430x120
Weight incl. Packaging:	1.8 kg
Content Master Package:	5
Dimensions of Master Package:	640x480x480 mm
Weight Master Package:	10,3 kg
Product Line:	Advance Line
Warranty	2 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557802800

Information and Downloads:

