


Placida Clou 225 18-830-860-1800LM OneFitAll



Technical Details:

Luminous Flux:	1806 lm
Light Yield:	100 lm/W
Light Temperature:	2800,4000,6000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	96
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz
Power Consumption:	Power Select (6, 12, 18 W)
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Kabel mit Klemmen
Switching Cycles:	>50.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-20°C - 50°C

Dimensions:	225x19 mm
Cut-Out Dimensions:	65-210 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20 (44 room side)
IK Code:	04
Housing Color	black
Housing Material:	plastic
Special Feature of Housing:	Farbwahlschalter 830-860
Cover:	opal
Net Weight:	400 g
Type of Packaging:	box
Dimensions of Packaging:	231x232x32
Weight incl. Packaging:	0.492 kg
Content Master Package:	20
Dimensions of Master Package:	650x240x245 mm
Weight Master Package:	10,15 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	30.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE
Barcode:	4250557823690
Über Schalter wählb. Lichtfarbe 2800, 4000, 5700 K	
Für gesägte Ausschnitte 65-210mm rund 150mm eckig	
Aufputzmontage möglich mediums Bügel	
Klemmterminal, leichte, schnelle Montage	

Information and Downloads:



