


Rotura 350 30-830-2700LM



Technical Details:

Luminous Flux:	2700 lm
LED Output:	29 W
Light Yield:	90 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥84 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 33-46V, 750mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	350x50 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	20 (54 room side)
Housing Color	white
Housing Material:	aluminum
Coating:	powder-coated
Cover:	clear prismatic
Net Weight:	2754 g
Type of Packaging:	box
Weight incl. Packaging:	2.95 kg
Content Master Package:	6
Dimensions of Master Package:	595x595x400 mm
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,SELV
Barcode:	4250557823270
integr. Motion sensor: optional/ on demand	
Dali Driver: optional/ on demand	
Fangseil und Drehverschluß	

Information and Downloads:



