


Spila MKII round 600 15-840-1400LM switch



Technical Details:

Luminous Flux:	1400 lm
LED Output:	15 W
Light Yield:	93 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	133 °
Light Emission:	
LED-Chip:	SMD 2835
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	15 W
Contains Driver:	✓
Power Factor (PF):	>0.6
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>25.000
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	600x65x53 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	44
IK Code:	04
Housing Color	white
Housing Material:	plastic
Special Feature of Housing:	with switch
Cover:	opal
Net Weight:	354 g
Type of Packaging:	box
Dimensions of Packaging:	620x60x75
Weight incl. Packaging:	0.457 kg
Content Master Package:	10
Dimensions of Master Package:	650x310x170 mm
Weight Master Package:	4,7 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	30.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE
Barcode:	4250557817705
mit seitlichem Schalter	

Information and Downloads:

