



Vatura 20,5-860-1630LM



Technical Details:

Luminous Flux:	1630 lm
LED Output:	20 W
Light Yield:	82 lm/W
Light Temperature:	6000 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Light Emission:	downward
LED-Chip Manufacturer:	Samsung
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	20 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>25.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	340x100 mm
Mounting:	ceiling,wall
Montageart:	recessed
IP Class:	44
IK Code:	10
Housing Color	white
Housing Material:	plastic
Cover:	opal
Net Weight:	1370 g
Type of Packaging:	box
Dimensions of Packaging:	355x355x110
Weight incl. Packaging:	1.66 kg
Content Master Package:	5
Dimensions of Master Package:	560x365x370 mm
Weight Master Package:	8,4 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,D
Barcode:	4250557809076
Ideal für Flure und Treppenhäuser	
Perfect for corridors and staircase hous	
Kann im Freien unter Vordächer verwendet werden!	
Can be used temporarily outside under canopies	

Information and Downloads:

