


# Wega Circle 1000-100-840-10000LM DALI DIM



## Technical Details:

|                                    |                        |
|------------------------------------|------------------------|
| Luminous Flux:                     | 10000 lm               |
| LED Output:                        | 95 W                   |
| Light Yield:                       | 100 lm/W               |
| Light Temperature:                 | 4000 K                 |
| Light Color:                       | neutralwhite           |
| Color Rendering Index:             | ≥80 Ra                 |
| Color Consistency (SDCM):          | <4                     |
| Beam Angle:                        | 110 °                  |
| Unified Glare Rating (UGR):        | <21                    |
| Light Emission:                    | downward               |
| Dimmable:                          | ✓                      |
| Method of Dimming:                 | DALI                   |
| LED-Chip:                          | SMD 2835               |
| Ignition Time:                     | <0,5 s                 |
| Input Current:                     | AC 220 - 240V, 50/60Hz |
| Power Consumption:                 | 100 W                  |
| Contains Driver:                   | ✓                      |
| Driver Manufacturer:               | Inventronics           |
| Power Factor (PF):                 | >0.9                   |
| Input Driver:                      | terminal               |
| CC/CV:                             | CC                     |
| Input Lamp:                        | Terminal               |
| Switching Cycles:                  | >100.000               |
| Electrical Protection Class:       | I                      |
| Compatible with Emergency Current: | ✓                      |
| Ambient Temperature (TA):          | -20°C - 45°C           |
| Storage Temperature:               | -20°C - 55°C           |

|                                                    |                  |
|----------------------------------------------------|------------------|
| Dimensions:                                        | 1000x82 mm       |
| Mounting:                                          | ceiling,wall     |
| Montageart:                                        | surface mounted  |
| IP Class:                                          | 20               |
| IK Code:                                           | 03               |
| Housing Color                                      | black            |
| Housing Material:                                  | aluminum         |
| Coating:                                           | powder-coated    |
| Cover:                                             | prismatic        |
| Net Weight:                                        | 15470 g          |
| Type of Packaging:                                 | box              |
| Weight incl. Packaging:                            | 18.22 kg         |
| Content Master Package:                            | 1                |
| Dimensions of Master Package:                      | 1060x120x1060 mm |
| Weight Master Package:                             | 18,22 kg         |
| Product Line:                                      | Advance Line     |
| Warranty                                           | 5 years          |
| Operating Hours:                                   | 50.000 h L80/B20 |
| Disposal Obligation:                               | ✓                |
| Customs Tariff Number:                             | 9405423990       |
| Certifications                                     | CE,SELV          |
| Barcode:                                           | 4250557823188    |
| mit opt. Zubehör als Pendelleuchte zu verwenden    |                  |
| Can be used with opt. accessories as pendant light |                  |
| Fangseil und Drehhalterung                         |                  |
| Dali dimmbarer Treiber                             |                  |

