PLANETA CLOU HighBay 120-200-830-850-35000LM 175lm/W max.DIM 0-10V Zhaga Book 18 OneFitAll

Technical Details:

Luminous Flux:	35000 lm		**Dimensions:**	330x140 mm
LED Output:	200 W		**Mounting:**	Decke
Light Yield:	180 lm/W		**Montageart:**	surface mounted
Light Temperature:	3000, 4000, 5000 K		**IP Class:**	66
Light Color:	CCT Select		**IK Code:**	08
Color Rendering Index:	≥80 Ra		**Housing Color**	grey
Color Consistency (SDCM):	<4		**Housing Color (RAL Code):**	similar 9006
Unified Glare Rating (UGR):	<25		**Housing Material:**	aluminum
Light Emission:	downward		**Coating:**	lacquered
Dimmable:	✓		**Special Feature of Housing:**	Zhaga Book 18 socket
Method of Dimming:	1-10V,PWM		**Cover:**	Lens
LED-Chip Manufacturer:	Liteon		**Net Weight:**	2300 g
LED-Chip:	SMD 5050		**Type of Packaging:**	box
Number of LED:	320		**Dimensions of Packaging:**	357x357x125
Ignition Time:	<0,5 s		**Weight incl. Packaging:**	2.89 kg
Input Current:	AC 100-277V, 0,25-1mA, 50/60Hz		**Content Master Package:**	1
Power Consumption:	Power Select (120, 150, 200 W)		**Dimensions of Master Package:**	365x360x150 mm
Contains Driver:	✓		**Weight Master Package:**	2,89 kg
Driver Manufacturer:	Sosen		**Product Line:**	Advance Line
Power Factor (PF):	>0.95		**Warranty**	5 years
Input Driver:	cable with flying leads		**Operating Hours:**	100.000 h L80/B10
Output of Driver:	DC 180-300V		**Disposal Obligation:**	✓
CC/CV:	CC		**Customs Tariff Number:**	9405119090
Output Current Adjustable:	✓		**Certifications**	CE,LM80
Input Lamp:	cable with flying leads		**Barcode:**	4250557827513
Switching Cycles:	>100.000		Alugehäuse mit hoher Wärmeleitfähigkeit	
			TGIC Beschichtung/Coating	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Compatible with Emergency Current:	✓	
Ambient Temperature (TA):	-40°C - 50°C	
Storage Temperature:	-40°C - 80°C	

0-10V PWM Dim und 12V DC Ausgang für Sensor

integr. Zhaga Book 18 socket

Information and Downloads: