

SATURNA PRO HighBay 100-200-840-40000LM DALI D4i Dim UGR20-25 BEG 200lm/W Zhaga Book 18 Adapter

NEW



Technical Details:

| | |
|-----------------------------|---|
| Luminous Flux: | 40000 lm |
| LED Output: | 200 W |
| Light Yield: | 205 lm/W |
| Light Temperature: | 4000 K |
| Light Color: | neutralwhite |
| Color Rendering Index: | ≥80 Ra |
| Color Consistency (SDCM): | <5 |
| Beam Angle: | 90 ° |
| Unified Glare Rating (UGR): | <22 |
| Light Emission: | downward |
| Dimmable: | ✓ |
| Method of Dimming: | 0-10V,DALI,Push-Dim |
| LED-Chip Manufacturer: | Liteon |
| LED-Chip: | SMD 5050 |
| Number of LED: | 400 |
| Ignition Time: | <0,5 s |
| Input Current: | AC 100-277V, 0,25-1mA, 50/60Hz |
| Power Consumption: | Power Select (100,120, 140,160,180,200 W) |
| Contains Driver: | ✓ |
| Power Factor (PF): | >0.96 |
| Input Driver: | cable with flying leads |
| Output of Driver: | DC 140-260V |
| CC/CV: | CC |
| Output Current Adjustable: | ✓ |
| Input Lamp: | terminal |
| Switching Cycles: | >100.000 |

| | |
|---|-------------------------------|
| Dimensions: | 390x134 mm |
| Mounting: | Decke |
| Montageart: | surface mounted |
| IP Class: | 66 |
| IK Code: | 10 |
| Housing Color | grey |
| Housing Color (RAL Code): | similar 9006 |
| Housing Material: | Aluminium ADC12 +PC Linse |
| Coating: | powder-coated |
| Special Feature of Housing: | Zhaga Book 18 Sockel |
| Cover: | Lens |
| Net Weight: | 3550 g |
| Type of Packaging: | box |
| Dimensions of Packaging: | 410x410x150 |
| Weight incl. Packaging: | 4.35 kg |
| Content Master Package: | 1 |
| Dimensions of Master Package: | 410x410x160 mm |
| Weight Master Package: | 4,35 kg |
| Product Line: | Premio Line |
| Warranty | 5 years |
| Operating Hours: | 100.000 h L80/B10 |
| Disposal Obligation: | ✓ |
| Customs Tariff Number: | 9405119090 |
| Certifications | CE,LM80 |
| Barcode: | 4250557827575 |
| Power Select: | 100, 120, 140, 160, 180, 200W |
| TGIC Beschichtung/Coating, RG1, THD<15% | |

| | |
|---------------------------|--------------|
| Ambient Temperature (TA): | -40°C - 55°C |
| Storage Temperature: | -40°C - 70°C |

Dali 2 DIM 12V DC Ausgang für Sensor Zhaga Book 18

Dustfree design , D4i Dali Data Output

Information and Downloads:

