


Exima Line 1200 50-860-5250LM



Technical Details:

Luminous Flux:	5250 lm
LED Output:	48 W
Light Yield:	105 lm/W
Light Temperature:	6000 K
Light Color:	cold white
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	130 °
Light Emission:	downward
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	1380
Ignition Time:	<0,5 s
Input Current:	AC 100 - 277V, 230mA, 50/60Hz
Power Consumption:	50 W
Contains Driver:	✓
Driver Manufacturer:	Sosen
Power Factor (PF):	>0.98
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	cable with flying leads
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-40°C - 55°C

Dimensions:	1285x126x90 mm
Mounting:	ceiling,wall
IP Class:	66
IK Code:	10
Housing Color	silvergrey
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	explosion protected
Cover:	opal
Net Weight:	7500 g
Type of Packaging:	box
Dimensions of Packaging:	1340x190x170
Weight incl. Packaging:	8.63 kg
Content Master Package:	1
Dimensions of Master Package:	1340x190x170 mm
Weight Master Package:	8,63 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557809908
ATEX zertifiziert durch Produzent	
EX Schutzzone: 1+2/21+22	
Power Link: in/out by Atex cable glands	
Atex: II 2 G Ex emb IIC T6 Gb	
Atex II 2 D Ex tb IIIC T80°C Db - IP66	

Information and Downloads:



