


Alvera Line MKII 600 20-840-2700LM DIM



Technical Details:

Luminous Flux:	2700 lm
LED Output:	20 W
Light Yield:	135 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V,PWM,Poti
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 100-277V, 50Hz
Power Consumption:	20 W
Contains Driver:	✓
Driver Manufacturer:	Lifud LF-GLD025YS
Power Factor (PF):	>0.95
Input Driver:	terminal
Output of Driver:	DC 30-40V, 500mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	625x85x78 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	10
Housing Color	white
Housing Material:	aluminum
Special Feature of Housing:	opt. Polycarbonat Cover
Cover:	opal
Net Weight:	1335 g
Type of Packaging:	box
Dimensions of Packaging:	695x92x82
Content Master Package:	4
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	50.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80,SELV,CB
Einfache, und schnelle Montage In/out	
Schnellverschluß Endkappen	
CE, UL, FCC, LM80, TM21	
dimmbare Version: 1-10V, PWM, Rx Poti	
optional auch mit Durchgangsverdrahtung 3 x 2,5mm²	

Information and Downloads:

