

Ekova 150 50-840-7500lm



Technical Details:

Luminous Flux:	7500 lm
LED Output:	50 W
Light Yield:	150 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Light Emission:	downward
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 350mA, 50/60Hz, DC 180-264V
Power Consumption:	50 W
Contains Driver:	✓
Driver Manufacturer:	Lifud
Power Factor (PF):	>0.9
Input Driver:	terminal
Output of Driver:	DC 137V, 350mA
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Loop-Through Cabling:	✓
Ambient Temperature (TA):	-20°C - 40°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1510x90x72 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	grey
Housing Material:	Polycarbonat
Special Feature of Housing:	schlagfest Edelstahlclips
Cover:	prismatic
Net Weight:	1684 g
Type of Packaging:	box
Weight incl. Packaging:	1.87 kg
Content Master Package:	9
Dimensions of Master Package:	1525x281x243 mm
Weight Master Package:	18,2 kg
Product Line:	Essential Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE
Barcode:	4250557823706
Efficiency: 90%, THD 20%, Inrush: 30A&190µs-230Vac	
Geeignet für Zentral Batterie Notstrom DC	
Edelstahlverschlüsse, Durchgangsverdrahtung	
Anzahl/Sicherungsautom: B10: 20 , B16: 32, C16: 54	
Nicht zur Verwendung im Außenbereich geeignet	

Information and Downloads:

