

# Xona Line 1280 31-840-4000LM



## Technical Details:

|                                    |                                   |
|------------------------------------|-----------------------------------|
| Luminous Flux:                     | 4000 lm                           |
| LED Output:                        | 30 W                              |
| Light Yield:                       | 129 lm/W                          |
| Light Temperature:                 | 4000 K                            |
| Light Color:                       | neutralwhite                      |
| Color Rendering Index:             | ≥85 Ra                            |
| Color Consistency (SDCM):          | <3                                |
| Beam Angle:                        | 120 °                             |
| Light Emission:                    | downward                          |
| LED-Chip:                          | SMD 2835                          |
| Ignition Time:                     | <0,5 s                            |
| Input Current:                     | AC 220-240V, 50/60Hz, DC 180-240V |
| Power Consumption:                 | 31 W                              |
| Contains Driver:                   | ✓                                 |
| Power Factor (PF):                 | >0.95                             |
| Input Driver:                      | terminal                          |
| Input Lamp:                        | Terminal                          |
| Switching Cycles:                  | >100.000                          |
| Electrical Protection Class:       | II                                |
| Compatible with Emergency Current: | ✓                                 |
| Ambient Temperature (TA):          | -20°C - 45°C                      |
| Storage Temperature:               | -20°C - 55°C                      |

|                                                     |                   |
|-----------------------------------------------------|-------------------|
| Dimensions:                                         | 1280x57x67 mm     |
| Mounting:                                           | ceiling,wall      |
| Montageart:                                         | surface mounted   |
| IP Class:                                           | 66                |
| IK Code:                                            | 09                |
| Housing Color                                       | hellgrey          |
| Housing Material:                                   | Polycarbonat      |
| Special Feature of Housing:                         | drehbare Endkappe |
| Cover:                                              | opal              |
| Net Weight:                                         | 1120 g            |
| Type of Packaging:                                  | box               |
| Dimensions of Packaging:                            | 1300x60x70        |
| Weight incl. Packaging:                             | 1.497 kg          |
| Content Master Package:                             | 10                |
| Dimensions of Master Package:                       | 1350x470x200 mm   |
| Weight Master Package:                              | 15,5 kg           |
| Product Line:                                       | Advance Line      |
| Warranty                                            | 5 years           |
| Operating Hours:                                    | 50.000 h L80/B10  |
| Disposal Obligation:                                | ✓                 |
| Customs Tariff Number:                              | 9405114090        |
| Certifications                                      | CE,LM80           |
| Barcode:                                            | 4250557818887     |
| optional mit Bewegungsmelder und Notstrombetrieb    |                   |
| on option with Emergency light function and sensor  |                   |
| Vergleichbare Helligkeit: wie 2 x 36W T8 Röhre      |                   |
| similar brightness as 2 x 36W T8 flourescent tube   |                   |
| Master/Slave option, "D" für Oberflächentemp. <90°C |                   |

## Information and Downloads:

