Technical Data Sheet


Order number: LG30821

LITEGEAR
LED Lighting Solutions

Cappila POULTRY 1150 30-RED-840-3900lm internal wire through terminals 2 x 0-10V Control









Technical Details:

Luminous Flux:	3900 lm
LED Output:	26 W
Light Yield:	130 lm/W
Light Temperature:	4000 + 625nm red K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	120 °
Unified Glare Rating (UGR):	<30
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	0-10V,1-10V
LED-Chip Manufacturer:	Hongli
LED-Chip:	SMD 2835
Number of LED:	216
Ignition Time:	<1 s
Input Current:	AC 200 - 240V, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	AIDimming
Power Factor (PF):	>0.97
Input Driver:	terminal
Output of Driver:	DC 9-42V, 300-750mA
CC/CV:	CC
Input Lamp:	Terminal
Switching Cycles:	>200.000
Electrical Protection Class:	I

Dimensions:	75x1152 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	67
IK Code:	10
Housing Color	white/silver
Housing Material:	Polycarbonat
Special Feature of Housing:	Tube
Cover:	opal
Net Weight:	2000 g
Type of Packaging:	box
Dimensions of Packaging:	1310x80x80
Weight incl. Packaging:	2.3 kg
Content Master Package:	6
Dimensions of Master Package:	1330x260x180 mm
Weight Master Package:	14 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	54.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405114090
Certifications	CE,LM80
Barcode:	4250557825304
Rohrleuchte 2 x 0-10V Dim Eingänge	
Tube Light 2 x 0-10V dimming inputs	
Edelstahlendkappen/stainless steel	
Durchgangsverdrahtung/power trough	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

Storage Temperature:	-20°C - 60°C

Information and Downloads: