


Technical Data Sheet

Order number: LG14170

Movara MKII 70/38-927-3230LM WH







Technical Details:

Luminous Flux:	3230 lm
LED Output:	38 W
Light Yield:	85 lm/W
Light Temperature:	2700 K
Light Color:	warmwhite
Color Rendering Index:	≥90 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90x60 °
Light Emission:	
LED-Chip Manufacturer:	Luminus
LED-Chip:	COB
Number of LED:	1
Ignition Time:	<0,5 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	38 W
Contains Driver:	✓
Driver Manufacturer:	Osram
Power Factor (PF):	>0.98
Input Driver:	lighting track
Output of Driver:	DC 33-42V, 1050mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Power rail
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C

Dimensions:	193x70x170 mm
Mounting:	Decke
Montageart:	surface mounted
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	white
Housing Color (RAL Code):	similar 9010
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	3-Phase Track Adapter
Cover:	clear
Net Weight:	900 g
Type of Packaging:	box
Dimensions of Packaging:	196*75*175
Weight incl. Packaging:	0.95 kg
Content Master Package:	16
Dimensions of Master Package:	410*320*370 mm
Weight Master Package:	16 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	35.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80
Barcode:	4250557813844

Wallwasher Tracklight

für Werbebanner oder Verkaufsregale

for banners or shelfs

Anzahl/Qty. 16A fuse: 25 pcs.

Information and Downloads:

