Technical Data Sheet

Order number: LG11428

Performa 36/28-840-2550LM







Technical Details:

Luminous Flux:	2550 lm
LED Output:	26 W
Light Yield:	91 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	36 °
Swappable Reflector:	✓
LED-Chip Manufacturer:	Sharp
LED-Chip:	COB
Ignition Time:	<1 s
Input Current:	AC 220 - 240V, 50/60Hz
Power Consumption:	28 W
Contains Driver:	✓
Power Factor (PF):	>0.9
Input Driver:	lighting track
Output of Driver:	DC 36V, 700mA
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 45°C

Mounting:	Decke
Pivot Range pan:	355 °
Pivot Range tilt:	90 °
IP Class:	20
Housing Color	silver
Housing Material:	aluminum
Coating:	powder-coated
Net Weight:	1697 g
Type of Packaging:	box
Weight incl. Packaging:	1.697 kg
Content Master Package:	8
Dimensions of Master Package:	505x280x545 mm
Weight Master Package:	14,2 kg
Product Line:	Premio Line
Warranty	3 years
Operating Hours:	50.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE
Barcode:	4250557806327

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de