Technical Data Sheet

Order number: LG32320DA

LITEGEAR
LED Lighting Solutions

VERSALINK MKII 90-1500 15-75W-CCT-Select-12350LM Flood DALI DIM





Technical Details:

Luminous Flux:	12350 lm
LED Output:	67.5 W
Light Yield:	165 lm/W
Light Temperature:	3000, 4000, 5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	90 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	San'an
LED-Chip:	SMD 2835
Number of LED:	360
Ignition Time:	<0,5 s
Input Current:	AC 200-240V, 50/60Hz, DC 180-264V
Power Consumption:	Power Select (15-75W W)
Contains Driver:	✓
Driver Manufacturer:	Boke
Power Factor (PF):	>0.97
Input Driver:	plug connector
Output of Driver:	DC 54-230V, 100-550mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	Steckverbinder 3-polig
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-25°C - 45°C
Storage Temperature:	-30°C - 80°C

Dimensions:	1536x74x31 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	20
IK Code:	06
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	PMMA Linse
Cover:	klar mit Linsen
Net Weight:	1300 g
Type of Packaging:	box
Weight incl. Packaging:	1.46 kg
Content Master Package:	8
Dimensions of Master Package:	1515x235x205 mm
Weight Master Package:	11,7 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	88.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557825168
Einfache Montage in 22 verschiedene Tragprofile	
justierbare Leuchtenlänge 1458-1536mm	
CCT Select: 3000, 4000, 5000K	
Power Select 15-75W passenden Stecker mitbestellen	
max. 30 Leuchten an einem 16A C Sicherungsutomaten	

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de

