

# Xona Maxima Basic Unit 150SP 35-860-5300LM



## Technical Details:

|                              |                                              |
|------------------------------|----------------------------------------------|
| Luminous Flux:               | 5300 lm                                      |
| LED Output:                  | 33 W                                         |
| Light Yield:                 | 151 lm/W                                     |
| Light Temperature:           | 6000 K                                       |
| Light Color:                 | cold white                                   |
| Color Rendering Index:       | ≥80 Ra                                       |
| Color Consistency (SDCM):    | <4                                           |
| Beam Angle:                  | 30 °                                         |
| Unified Glare Rating (UGR):  | <16                                          |
| Light Emission:              | downward                                     |
| LED-Chip Manufacturer:       | Epistar                                      |
| LED-Chip:                    | SMD 2835                                     |
| Ignition Time:               | <0,5 s                                       |
| Input Current:               | AC 170 -264V, 230mA, 50/60Hz,<br>DC 170-230V |
| Power Consumption:           | 35 W                                         |
| Contains Driver:             | ✓                                            |
| Driver Manufacturer:         | Litegear                                     |
| Power Factor (PF):           | >0.95                                        |
| Input Driver:                | terminal                                     |
| Output of Driver:            | DC 55-80V, 430mA                             |
| CC/CV:                       | CC                                           |
| Input Lamp:                  | plug connector                               |
| Switching Cycles:            | >100.000                                     |
| Electrical Protection Class: | I                                            |
| Ambient Temperature (TA):    | -20°C - 50°C                                 |

|                               |                   |
|-------------------------------|-------------------|
| Dimensions:                   | 1498,5x70x39,4 mm |
| Mounting:                     | Decke             |
| Montageart:                   | surface mounted   |
| IP Class:                     | 30                |
| IK Code:                      | 02                |
| Housing Color                 | white             |
| Housing Material:             | steel             |
| Cover:                        | clear             |
| Net Weight:                   | 1670 g            |
| Type of Packaging:            | box               |
| Weight incl. Packaging:       | 1.85 kg           |
| Content Master Package:       | 10                |
| Dimensions of Master Package: | 1550x390x210 mm   |
| Weight Master Package:        | 19,8 kg           |
| Product Line:                 | Advance Line      |
| Warranty                      | 5 years           |
| Operating Hours:              | 50.000 h L70/B10  |
| Disposal Obligation:          | ✓                 |
| Customs Tariff Number:        | 9405499090        |
| Certifications                | CE,TÜV,ENEC,LM80  |
| Barcode:                      | 4250557815114     |

## Information and Downloads:



