

# Xona Maxima Basic Unit 150FL 50-860-9000LM DALI 180lm/W



## Technical Details:

|                                    |                                             |
|------------------------------------|---------------------------------------------|
| Luminous Flux:                     | 9000 lm                                     |
| LED Output:                        | 47 W                                        |
| Light Yield:                       | 170 lm/W                                    |
| Light Temperature:                 | 5700 K                                      |
| Light Color:                       | cold white                                  |
| Color Rendering Index:             | ≥83 Ra                                      |
| Color Consistency (SDCM):          | <4                                          |
| Beam Angle:                        | 90 °                                        |
| Unified Glare Rating (UGR):        | <24                                         |
| Light Emission:                    | downward                                    |
| Dimmable:                          | ✓                                           |
| Method of Dimming:                 | DALI                                        |
| LED-Chip Manufacturer:             | Epistar                                     |
| LED-Chip:                          | SMD 2835                                    |
| Ignition Time:                     | <0,5 s                                      |
| Input Current:                     | AC 170 - 264V, 0,33mA, 50/60Hz, DC 170-230V |
| Power Consumption:                 | 53 W                                        |
| Contains Driver:                   | ✓                                           |
| Driver Manufacturer:               | Litegear                                    |
| Power Factor (PF):                 | >0.96                                       |
| Input Driver:                      | terminal                                    |
| Output of Driver:                  | DC 55-80V, 0,62mA                           |
| CC/CV:                             | CC                                          |
| Input Lamp:                        | plug connector                              |
| Switching Cycles:                  | >100.000                                    |
| Electrical Protection Class:       | I                                           |
| Compatible with Emergency Current: | ✓                                           |
| Ambient Temperature (TA):          | -20°C - 50°C                                |

|                               |                   |
|-------------------------------|-------------------|
| Dimensions:                   | 1498,5x70x39,4 mm |
| Mounting:                     | Decke             |
| Montageart:                   | surface mounted   |
| IP Class:                     | 30                |
| IK Code:                      | 02                |
| Housing Color                 | white             |
| Housing Material:             | steel             |
| Coating:                      | coated            |
| Cover:                        | clear             |
| Net Weight:                   | 1680 g            |
| Type of Packaging:            | none              |
| Weight incl. Packaging:       | 1.68 kg           |
| Content Master Package:       | 10                |
| Dimensions of Master Package: | 1570x400c210 mm   |
| Weight Master Package:        | 19,8 kg           |
| Product Line:                 | Advance Line      |
| Warranty                      | 5 years           |
| Operating Hours:              | 60.000 h L80/B20  |
| Disposal Obligation:          | ✓                 |
| Customs Tariff Number:        | 9405119090        |
| Certifications                | CE,TÜV,ENEC,LM80  |
| Barcode:                      | 4250557824611     |

