

Xona Maxima Basic Unit 150WFL 50-840-8900LM DALI DIM



Technical Details:

Luminous Flux:	9000 lm
LED Output:	50 W
Light Yield:	180 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	120 °
Unified Glare Rating (UGR):	<22
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip Manufacturer:	Ebright
LED-Chip:	SMD 2835
Number of LED:	245
Ignition Time:	<1 s
Input Current:	AC 220-240V, 245-350mA, 50/60Hz, DC 220-240V
Power Consumption:	Power Select (35, 40, 45, 50 W)
Contains Driver:	✓
Driver Manufacturer:	CoreShine
Power Factor (PF):	>0.96
Input Driver:	terminal
Output of Driver:	DC 55-80V, 620mA
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	plug connector
Switching Cycles:	>100.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓

Dimensions:	1499x70x40 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	40
IK Code:	03
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	steel
Coating:	coated
Special Feature of Housing:	geringe Blendung opal
Cover:	opal
Net Weight:	1650 g
Type of Packaging:	none
Dimensions of Packaging:	1570x430x210
Weight incl. Packaging:	1.85 kg
Content Master Package:	10
Dimensions of Master Package:	1570x430x210 mm
Weight Master Package:	18,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,ENEC,LM80,CB
Barcode:	4250557827605
Power Select und Dali 2.0 Dim	
sehr breiter Abstrahlungsbereich	
Ideal für Kleinteilelager, Produktionsbereiche	

Storage Temperature:

-40°C - 85°C

Information and Downloads:

