Technical Data Sheet

Order number: LG31568DA

LITEGEAR
LED Lighting Solutions

Xona Maxima Basic Unit 150FL 70-951-10500LM DALI 2 Dim Real-Daylight Colour







Technical Details:

Luminous Flux:	10500 lm
Light Yield:	150 lm/W
Light Temperature:	5100 K
Light Color:	daylight
Color Rendering Index:	≥95 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Unified Glare Rating (UGR):	<26
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	DALI,Push-Dim
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Input Current:	AC 180 - 264V, 50/60Hz, DC 170-230V
Power Consumption:	Power Select (55, 60, 65, 70 W)
Contains Driver:	✓
Driver Manufacturer:	Litegear
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	1498,5x70x39,4 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	33
IK Code:	02
Housing Color	white
Housing Material:	steel
Coating:	coated
Cover:	Linse gefrostet
Net Weight:	1780 g
Type of Packaging:	box
Weight incl. Packaging:	1.85 kg
Content Master Package:	10
Dimensions of Master Package:	1550x390x210 mm
Weight Master Package:	20 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	65.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,TÜV,ENEC,LM80
Real Daylight Proof Colour Light	
Farbraumkoordinaten: x = 0,3478 / y = 0,3595	
zur Abmusterung nach ISO 3664:2009	

Information and Downloads: