


Campa Flex Floodlight FL75-840-9500LM



Technical Details:

Luminous Flux:	9200 lm
LED Output:	75 W
Light Yield:	123 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<20
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 5050
Ignition Time:	<0,5 s
Input Current:	AC 100 - 265V, 50/60Hz
Power Consumption:	75 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
CC/CV:	CC
Switching Cycles:	>100.000
Electrical Protection Class:	I
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 45°C

Dimensions:	225x320x130 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular, swivelling
Cover:	frosted
Net Weight:	3100 g
Type of Packaging:	box
Content Master Package:	4
Weight Master Package:	17 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE,LM80
Barcode:	4250557813325
Akzo Nobel Beschichtung	

Information and Downloads:

