

CONLUX Floodlight NB1250-740-175000LM




450W/500W/600W 900W/1000W/1250W 1350W/1500W



Dimmbar
1-10V

Accessory			
Control Gear	Model	Power	Input Voltage
Matrix	Matrix-340-450/500W	450W/500W	100-240VAC
	Matrix-340-600W	600W	
	Matrix-340-900/1000W	900W/1000W	
	Matrix-340-1250W	1250W	
	Matrix-340-1350/1500W	1350W/1500W	



Matrix-340-450W
Matrix-340-500W
Matrix-340-600W

Technical Details:

Luminous Flux:	175300 lm
Light Yield:	140 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥70 Ra
Color Consistency (SDCM):	<3
Beam Angle:	60 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V
LED-Chip Manufacturer:	Seoul Semiconductor
LED-Chip:	SMD 3535
Ignition Time:	<0,5 s
Input Current:	AC 100 - 240V, 50/60Hz
Power Consumption:	1250 W
Contains Driver:	✓
Power Factor (PF):	>0.95
Input Driver:	terminal
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>250.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	631x585x453 mm
Montageart:	surface mounted
IP Class:	66
IK Code:	10
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Special Feature of Housing:	modular
Cover:	Lens
Net Weight:	22900 g
Type of Packaging:	box
Content Master Package:	1
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	104.000 h L90B50
Disposal Obligation:	✓
Customs Tariff Number:	9405421000
Certifications	CE,ENEC,LM80,ERP,CB
Barcode:	4250557824666
1-10V dimmbar optional Dali dim	
Akzo Nobel Beschichtung	

Information and Downloads:



