


Luna Plane IP66 Floodlight 150-840-20400LM



Technical Details:

Luminous Flux:	20400 lm
LED Output:	145 W
Light Yield:	136 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Beam Angle:	120 °
Light Emission:	
LED-Chip Manufacturer:	Cree
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	150 W
Contains Driver:	✓
Driver Manufacturer:	Meanwell
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 36 - 48V, 3100mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>50.000
Electrical Protection Class:	II
Compatible with Emergency Current:	✓
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 55°C

Dimensions:	400x340x90 mm
Mounting:	ceiling,wall
Montageart:	surface mounted
IP Class:	66
IK Code:	09
Housing Color	black
Housing Material:	aluminum
Coating:	powder-coated
Net Weight:	7600 g
Type of Packaging:	box
Dimensions of Packaging:	490x410x135
Weight incl. Packaging:	8.28 kg
Content Master Package:	2
Dimensions of Master Package:	415x285x510 mm
Weight Master Package:	19, kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	50.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405409990
Certifications	CE,TÜV,GS,ENEC,LM80
Barcode:	4250557808123
Meanwell Driver	

Information and Downloads:



