


Scheinwerfer Luna Plane IP66 Floodlight 72-840-8600LM



Technical Details:

Luminous Flux:	8600 lm
LED Output:	72 W
Light Yield:	119 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	120 °
Light Emission:	
LED-Chip Manufacturer:	Lumileds
LED-Chip:	SMD 2835
Number of LED:	120
Ignition Time:	<1 s
Input Current:	AC 90-305V, 335mA, 50/60Hz
Power Consumption:	72 W
Contains Driver:	✓
Driver Manufacturer:	Sosen
Power Factor (PF):	>0.95
Input Driver:	cable with flying leads
Output of Driver:	DC 28-56V, 350-2100mA
CC/CV:	CC
Input Lamp:	cable with plug
Switching Cycles:	>50.000
Ambient Temperature (TA):	-20°C - 50°C
Storage Temperature:	-40°C - 60°C

Dimensions:	330x265x75 mm
Mounting:	ceiling,wall,ground
Montageart:	surface mounted
IP Class:	66
IK Code:	08
Housing Color	silver
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	4800 g
Type of Packaging:	box
Dimensions of Packaging:	480x315x420
Weight incl. Packaging:	5.15 kg
Content Master Package:	4
Dimensions of Master Package:	480x315x420 mm
Weight Master Package:	20,6 kg
Product Line:	Advance Line
Warranty	3 years
Operating Hours:	82.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405421000
Certifications	CE,GS,LM80
Barcode:	4250557824079

Information and Downloads:



