
Technical Data Sheet

Order number: LG11930GR

Aversa 30-740-3960LM







Technical Details:

Luminous Flux:	3960 lm
LED Output:	28 W
Light Yield:	132 lm/W
Light Temperature:	4000 K
Light Color:	neutralwhite
Color Rendering Index:	≥74 Ra
Color Consistency (SDCM):	<6
Beam Angle:	150x80 °
Light Emission:	downward
LED-Chip Manufacturer:	Cree
LED-Chip:	SMD 3030
Ignition Time:	<0,5 s
Input Current:	AC 120 - 277V, 130mA, 50/60Hz
Power Consumption:	30 W
Contains Driver:	✓
Driver Manufacturer:	Philips
Power Factor (PF):	>0.93
Input Driver:	cable with flying leads
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-20°C - 55°C
Storage Temperature:	-40°C - 60°C

Dimensions:	600x260x110 mm
Pivot Range tilt:	90 °
IP Class:	66
IK Code:	09
Housing Color	betongrey
Housing Color (RAL Code):	similar 7023
Housing Material:	aluminum
Coating:	lacquered
Special Feature of Housing:	Top cover
Net Weight:	4682 g
Type of Packaging:	box
Dimensions of Packaging:	635x265x135
Weight incl. Packaging:	5.36 kg
Content Master Package:	1
Dimensions of Master Package:	635x265x135 mm
Weight Master Package:	5,432 kg
Product Line:	Premio Line
Warranty	5 years
Operating Hours:	100.000 h L70/B20
Disposal Obligation:	✓
Customs Tariff Number:	94051990
Certifications	CE,LM80
Barcode:	4250557820408
Mastaufnahme Ø: 60 mm	
SPD Überspannungsschutz integriert	
Philips Xitanium Driver 0,7A	
tempered glass	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de