

SOLVELA BRICK 6-730-900LM IP65



Technical Details:

Luminous Flux:	900 lm
LED Output:	6 W
Light Yield:	150 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<5
Beam Angle:	140x70 °
Light Emission:	downward
LED-Chip:	SMD 2835
Number of LED:	35
Ignition Time:	<1 s
Input Current:	DC 3,7V, 3000mAhmA
Power Consumption:	6 W
CC/CV:	CV
Switching Cycles:	>15.000
Ambient Temperature (TA):	-10°C - 45°C
Storage Temperature:	0°C - 50°C

Dimensions:	230x97x42,7 mm
Mounting:	Wand
Montageart:	surface mounted
IP Class:	65
Housing Color	white
Housing Material:	ABS+PC, Anti UV,V0 firep.
Special Feature of Housing:	Sensor 6m /Solarpanel
Cover:	Lens
Net Weight:	0.585 g
Type of Packaging:	box
Weight incl. Packaging:	0.653 kg
Content Master Package:	24
Dimensions of Master Package:	500x310x230 mm
Weight Master Package:	15,42 kg
Product Line:	Essential Line
Warranty	2 years
Operating Hours:	15.000 h L80/B20
Disposal Obligation:	✓
Customs Tariff Number:	9405413990
Certifications	CE
Barcode:	4250557822419
Solarleuchte für Wandmontage, modernes Design	
solar wall pack light stylish design, 2 work modes	
integrierter Bewegungssensor mit Dimmung/Standby	
integrated motion sensor 120° <6m	
replaceable battery pack 18650/3000mA/3,7V/11,1Wh	

Information and Downloads:

