Technical Data Sheet

Order number: LG59029

Cetara Office 6262 BAP 36-830-4320LM









Technical Details:

Luminous Flux:	4320 lm
LED Output:	35 W
Light Yield:	120 lm/W
Light Temperature:	3000 K
Light Color:	warmwhite
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<3
Beam Angle:	90 °
Unified Glare Rating (UGR):	<19
Light Emission:	downward
LED-Chip Manufacturer:	SANAN
LED-Chip:	SMD 4014
Number of LED:	216
Ignition Time:	<0,5 s
Power Consumption:	36 W
Power Factor (PF):	>0.95
Output of Driver:	DC 32-42V, 500-1000mA
CC/CV:	CC
Input Lamp:	plug connector
Switching Cycles:	>100.000
Ambient Temperature (TA):	-25°C - 45°C
Storage Temperature:	-40°C - 60°C

Dimensions:	620x620x10 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20 (44 room side)
IK Code:	07
Housing Color	white
Housing Color (RAL Code):	similar 9016
Housing Material:	aluminum
Coating:	powder-coated
Cover:	prismatic
Net Weight:	2270 g
Type of Packaging:	box
Dimensions of Packaging:	640x680x35
Weight incl. Packaging:	2.67 kg
Content Master Package:	5
Dimensions of Master Package:	655x705x200 mm
Weight Master Package:	14,5 kg
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L80/B10
Disposal Obligation:	✓
Customs Tariff Number:	9405 11 90 90
Certifications	CE
Barcode:	4250557819716
LED-Treiber nicht im Lieferumfang enthalten!	
without LED driver!	

Information and Downloads:

Änderungen vorbehalten
Technical details are subject to change
(c) 2017

Litegear GmbH
An Fürthenrode 45
52511 Geilenkirchen

Tel.: +49 (0)2451 48453-0
Fax: +49 (0)2451 48453-13
www.litegear.de